

WYKAZ MODELI ELEKTROZWÓR

| INDEKS | NAPIĘCIE | ZASILANIE | POBÓR PRĄDU | | | TYP PRACY | SIŁA TRZYMANIA | | | | | FUNKCJE DODATKOWE | | | | MONTAŻ | | |
|-------------|----------|------------------|-------------|-----------|-----------|-----------|----------------|-------|-------|-------|-------|-------------------|-----------------------|------------------------|----------|---------------|----------------|------------|
| | 12/24V | na prąd stały DC | 350/175mA | 400/200mA | 500/250mA | NO | 180kg | 200kg | 300kg | 400kg | 530kg | 750kg | monitoring zamknięcia | monitoring stanu drzwi | warystor | wodoodporność | nawierzchniowy | wpuszczany |
| MG300.180MR | • | • | • | | | • | • | | | | | | • | | • | | | • |
| MG300.300MR | • | • | | | • | • | | | | | | | • | | • | | | • |
| MG300.300M | • | • | | | • | • | | | | | | | | | • | | | • |
| MG300.180SR | • | • | • | | | • | • | | | | | | • | | • | | | • |
| MG300.300SL | • | • | | | • | • | | | • | | | | • | | • | | | • |
| MG300.300S | • | • | | | • | • | | | • | | | | | | • | | | • |
| MG500.S | • | • | | | • | • | | | | • | | | | | • | | | • |
| MG500.SL | • | • | | | • | • | | | | • | | | • | | • | | | • |
| MG500.SCL | • | • | | | • | • | | | | • | | | • | • | • | | | • |
| MG500.2S | • | • | | | • | • | | | | • | | | | | • | | | • |
| MSS.200S | • | • | | • | | • | | • | | | | | | | • | • | | • |
| MSS400SSR | • | • | | • | | • | | | • | | | | • | | • | • | | • |
| MSS.400SFR | • | • | | • | | • | | | • | | | | • | | • | • | | • |
| MSS.750SSR | • | • | | | • | • | | | | | • | | • | | • | • | | • |
| MSS.750SFR | • | • | | | • | • | | | | | • | | • | | • | • | | • |
| MSS.750SR | • | • | | | • | • | | | | | • | | • | | • | • | | • |